

6500-WATT UP TO 8000-WATT

Industrial Gasoline



GEN-6500-0MK1 shown with lifting hook, AW-5090-0003

Engineered for tough jobs, these 6500 to 8000-watt generators deliver reliable power with durable construction and essential safety features.

ALTERNATOR

- Total harmonic distortion (THD) less than 5%
- Copper windings

FRAME

- Powder coated wraparound frame (GEN-6500-0MK1 comes standard with wheel kit with 10-inch flat-free tires)
- Angled isolator design features four neoprene isolators

COMPONENTS


- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Equipped with CO detector (GEN-6500-0MK1)
- Large low tone muffler
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Idle control
- Voltmeter (GEN-7500-0MH0)
- Hour meter (Honda and Mi-T-M engine models)
- Heavy-duty industrial air cleaner
- USDA/USFS-approved spark arrestors

LIMITED WARRANTIES

- 2 year alternator
- 3 year Honda, Kohler and Mi-T-M engines

CERTIFICATION

- CSA Certified



GFCI 5-20R



NEMA L14-30R
120V/240V



NEMA L5-30R
120VAC

MODEL NUMBER	GEN-6500-MMM0+	GEN-6500-0MK1+	GEN-7500-0MH0+	GEN-8000-MMM0+
MAX. AC OUTPUT	7500 watts	7500 watts	7500 watts	8000 watts
RATED AC OUTPUT	6500 watts	6500 watts	6500 watts	7200 watts
DISPLACEMENT/ENGINE	420cc Mi-T-M OHV with electric start – sealed battery included	429cc Kohler CH440 OHV	389cc Honda GX390 OHV	420cc Mi-T-M OHV with electric start – sealed battery included
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	62.5/31.5	62.5/31.5	62.5/31.3	66.7/33.3
CONT. AMPS (120V/240V)	54.2/27.1	54.2/27.1	54.2/27.1	60.0/30.0
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
CIRCUIT BREAKERS	(2) 20A circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole	(2) 20A circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole	(2) 20A circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole	(2) 20A circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole
RATED SPEED	3600 RPM	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	85.0	78.2	80.0	85.0
FUEL CAPACITY	6.6 gallons	6.6 gallons	7.3 gallons	6.6 gallons
RUN TIME (AT FULL LOAD)	6.1 hours	6.1 hours	6.9 hours	5.4 hours
DIMENSIONS (LxWxH)	29x24.4x22.5in.	32.5x28x27.5in.	29x24.4x22.5in.	29x24.4x22.5in.
SHIP WT.	244 lb.	244 lb.	255 lb.	254 lb.
NET WT.	222 lb.	222 lb.	233 lb.	222 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating. *49 state engine and/or fuel tank. Not for sale in California.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	All models	AW-5090-0004	Lifting hook	All models except GEN-6500-0MK1
32-1289	Triple receptacle adapter	All models	AW-5740-0010	Wheel kit with flat-free tires	All models except GEN-6500-0MK1
AW-5090-0003	Lifting hook	GEN-6500-0MK1	AW-6000-1002	Equipment cover	All models